

SAVEMA 20 i&c&tr SERIES THERMAL TRANSFER OVERPRINTERS

32*40 I
53*40 I
Magnetic



Common Specifications for All Printers

Software: SAYASIS Template Design (Date and Time, Custom Formatted Date and Time, Text, Text Block, Merge Fields, Database Support, Counter, Logo, 1D / 2D Barcodes, GS-1 Barcodes, Table Creation Support and User-Friendly Interface)

Windows Driver Support, Teklynx Software (Code-soft, Labelview and Label Matrix Support), Emulator Support, Printer Management with SPPL (Savema Protocol) Commands, Printer Control with Remote Control)

Barcodes: 1D Barcodes (EAN-13, EAN-8, CODE 128, CODE 39, CODABAR, ITF 2of5, ITF 14, UPC-A, UPC-E ...), 2D Barcodes (Datamatrix, QR Code, PDF417, Aztec code...), GS-1 Barcodes (GS1-128, GS1-Datamatrix, GS1-Databar Barcodes)

Resolution: 300dpi (12 dots/mm) horizontally and vertically

Operating Temperature: 5 °C - 40 °C (41°F-104°F)

Memory: 5000 Template Storage Capacity, 1GB Internal Memory, Up to 16GB SD Memory Card Support, Up to 32GB USB Memory Support

Specifications	32*40 I (Intermittent)	53*40 I (Intermittent)
Print Area	32mm x 40mm	53mm x 40mm
Print Speed	50 - 300 mm/sec	
Production	100 prints/min.	
Ribbon Widths & Length	22mm, 35 mm (0,9" - 1,4") & 600 meters (656yards) loaded ribbon	35mm, 55 mm (1,4" - 2,2") & 600 meters (656yards) loaded ribbon
Power Supply	100/240V 50/60 Hz	
Air Supply (Bar)	Magnetic / Don't Need Air	
Input/Outputs	Print signal / Fault signal, Busy signal.	
Output Messages	Update Error, Contact Error, Ribbon Break / Not Found Error, Remaining Ribbon Quantity, Number of Printed Templates, Number of Prints per Minute	
Connection Types	Relay(NPN, PNP) - Photocell (NPN, PNP)	
Communications	RS-232, Ethernet, USB	
Ribbon Save Modes	Vertical & Horizontal Ribbon Save Modes	
Advanced Control	4.3" Touch Screen Control, Template Changing while Running, Print Position Adjustment, Contrast, Print Delay, Template-Specific Adjustment, Internal Contact Signal, Multi-print Contact Signal, Template Shifting, Template Rotation	
Operator Interface	4.3" 272x480 Pixels Resolution, Full-color display, Password protection on menus, Multi-language(18) support	
Weight (Printer)	5,6 Kg.	
Dimensions	175mm H x 190mm W x 197mm D	175mm H x 190mm W x 210mm D

